

Lenovo™ ThinkVision® T2254p Monitor

UNCOMPROMISED PERFORMANCE

Exceptional Display That Fuels Productivity



Lenovo™

Outstanding visuals are just the beginning with this sleek, high-performance monitor. 22" wide monitor delivers exceptional resolution, brightness and contrast across a wide-view screen that enhances productivity. Multiple connectivity options, ergonomic full-function stand and Green certifications make it an excellent all-around monitor for virtually any business environment.

WHY YOU SHOULD BUY THE LENOVO™ THINKVISION® T2254p MONITOR



Outstanding Visuals

The 22" 16:10 screen is perfect for any business content, displayed with 250 nits brightness and 1000:1 contrast for the darkest blacks and brightest colors with an anti-glare finish.



Multiple Connectivity Options

Ideal for multimonitor settings with VGA, HDMI™ 1.4 and DisplayPort™ 1.2 connectivity options, perfect for connecting a wide range of PCs and notebooks.



Ergonomic Design

The ergonomic full-function stand is perfect for collaboration. It supports the new ThinkCentre® Tiny Clamp bracket for easy set-up of ThinkCentre® Tiny at the back of the monitor. Practical cable management effectively manages desktop clutter.

THE LENOVO™ THINKVISION® T2254p MONITOR IS BEST SUITED FOR

1

Professionals in the fields of finance, healthcare, education and office administration.

2

Any enterprise or individual who is seeking a high-performance monitor with multiple connectivity options.

3

Organizations that require professional quality monitors that also deliver a green advantage.



Lenovo™ ThinkVision® T2254p Monitor

SPECIFICATIONS

DISPLAY		POWER CONSUMPTION	
Panel Size	22" Wide	Power Consumption	
Panel Type	TN	Typical	20 W
Backlight	WLED	Maximum	25 W
Viewable Area (Diagonal) (mm / inches)	558.8 / 22"	Sleep-Mode	0.5 W
Screen Dimensions (W x H) (mm)	473.76 x 296.1	Switch Off-Mode	0.5 W
Resolution	1680 x 1050	Heat Dissipation	
Aspect Ratio	16:10	Typical	68.2 Btu/h
Viewing Angle (H/V at CR 10:1)	170°/160°	Maximum	85.25 Btu/h
Maximum Brightness (Typical)	250 cd/m ²	Power Supply	Internal
Contrast Ratio (Typical)	1000:1	Power Voltage	90 VAC - 264 VAC, 1.5 A
Dynamic Contrast Ratio	3M:1	Voltage Dynamic Frequency	47 Hz - 63 Hz
Pixel Pitch (W x H) (mm)	0.282 x 0.282		
Dot/Pixel Per Inch (DP/PPI)	90		
Color Gamut (CIE 1931)	72%		
Color Gamut (CIE 1976)	86%		
Number of Colors	16.7 Million		
Response Time	5 ms (On/Off)		
Anti-Glare	Yes		
SIGNAL INPUT		DIMENSIONS (W x D x H)	
Video Input Signals	VGA, HDMI™ 1.4, DisplayPort™ 1.2	Size Packed	
Video Cables Supplied	VGA, DisplayPort™	(mm)	570 x 176 x 412
Video Cable Length	1.8 m	(inches)	22.44" x 6.93" x 16.22"
USB Hub	No	Size Unpacked with Stand	
USB Cable Supplied	No	(mm)	509.3 x 242.6 x 371.7
Audio-Out	Yes	(inches)	20.01" x 9.55" x 14.63"
SIGNAL INTERFACE / PERFORMANCE		Size Unpacked without Stand	
Horizontal Frequency	30 kHz - 81 kHz	(Monitor Head Only)	
Vertical Frequency	50 Hz - 75 Hz	(mm)	509.3 x 44 x 331.7
Native Resolution	1680 x 1050	(inches)	20.05" x 1.73" x 13.06"
Maximum Pixel Clock Speed / Bandwidth	205 MHz (VGA)	Distance from Table to Panel	
Default Color Temperature	7200K	(mm / inches)	
Preset Display Modes	28	Lowest Pixel at Bottom of Screen	57.78 / 2.28"
User-defined Display Modes	20	Highest Pixel at Top of Screen	353.88 / 13.93"
OSD Buttons	5	Stand Base Footprint Area (mm / inches)	240 x 240 / 9.45" x 9.45"
OSD Languages	8	Weight	
		Packed	Starting at 13.9 lbs (6.3 kg)
		Unpacked	Starting at 10.14 lbs (4.6 kg)
		Monitor Head Only	Starting at 6.28 lbs (2.85 kg)
ENVIRONMENTAL		MECHANICAL	
Temperature		Tilt Angle (Front / Back)	-5° - 30°
Operating	0°C - 45°C	Swivel Angle (Left / Right)	-45° - 45°
Non-operating	-20°C - 60°C (Non-Condensing)	Lift (mm)	110
Humidity		Pivot	0° - 90° (Clockwise)
Operating	10% - 80%	VESA® Mount (mm)	100 x 100
Non-operating	5% - 95% (Non-Condensing)	Kensington® Lock Slot	Yes
Altitude		Cable Management	Yes
Operating	8,000 ft	Ambient Light Sensor	No
Non-operating	40,000 ft	Bezel Color	Raven Black
Arsenic-Free Glass	Yes	Bezel Width	
PVC-Free	Yes	Sides (mm / inches)	17.1 / 0.67"
Mercury-Free	Yes	Top (mm / inches)	17.1 / 0.67"
PCC % of Plastic Resins	85%	Bottom (mm / inches)	17.1 / 0.67"
Low Halogen	No		
COMPLIANCE		WARRANTY AND AVAILABILITY	
EPEAT™	Gold	Warranty	3 Years
ENERGY STAR® Rating	7.0	Geography Availability	World-Wide
ULE	Gold		
TCO	Display 7.0		
TCO Edge	2.0		
TUV	Yes		
RoHS (EU 2002/95/EC)	Yes		
Windows Certification	Windows 10 / Windows 8.1 / Windows 8.0 / Windows 7		
China Energy Efficiency Standard	Tier 1 (New Standard Tier 2)		



WWW.LENOVO.COM

Lenovo reserves the right to alter product offerings and specifications at any time, without notice. Lenovo makes every effort to ensure accuracy of all information but is not liable or responsible for any editorial, photographic or typographic errors. All images are for illustration purposes only. For full Lenovo product, service and warranty specifications visit www.lenovo.com. Lenovo makes no representations or warranties regarding third party products or services. **Trademarks:** The following are trademarks or registered trademarks of Lenovo: Lenovo, the Lenovo logo, Rescue and Recovery, ThinkPad, ThinkCentre, ThinkStation, ThinkServer, ThinkVantage and ThinkVision. Microsoft, Windows and Vista are registered trademarks of Microsoft Corporation. Ultrabook, Celeron, Celeron Inside, Core Inside, Intel, Intel Logo, Intel Atom, Intel Atom Inside, Intel Core, Intel Inside, Intel Inside Logo, Intel vPro, Itanium, Itanium Inside, Pentium, Pentium Inside, vPro Inside, Xeon, Xeon Phi, and Xeon Inside are trademarks of Intel Corporation in the U.S. and/or other countries. Other company, product and service names may be trademarks or service marks of others. Battery life (and recharge times) will vary based on many factors including system settings and usage. Visit www.lenovo.com/lenovo/us/en/safecomp/ periodically for the latest information on safe and effective computing. ©2016 Lenovo. All rights reserved.